

HOLDS & HATCHES

All 5 hatch covers and tween decks – as appropriate, are operated hydraulically.

No.1 & 2 holds have single hydraulic folding hatch covers and tween deck lids, and capable of non sequential opening. No.2 to 5 holds are fitted with P&S hydraulic folding hatch covers which are capable of non-sequential opening, (i.e. half hatch and hold can be worked while containers are stowed in the other half of the hold).

No.1 Hatch has no centre-line division, Nos 2 to 5 Hatch Covers consist of Port & Stbd covers, and No.2, 3 & 4 holds are fitted with a full centre-line non-watertight bulkhead.

Clearance of Hatches (mtrs):

Hold		Tanktop	Tween Deck
No. 1	Center	5.45	5.94
No. 2	P&S	8.05	5.94
No. 3	P&S	13.015	--
No. 4	P&S	13.015	--
No. 5	P&S	13.050	--

Grain & Bale capacity:

No.	Grain (cubic m)		Bale (cubic m)	
	TD	LH	TD	LH
No.1	1,806.4	1,825.1	1,746.5	1,630.0
	hatch 280.7		hatch 280.7	
No.2	2,712.6	4,196.0	2,623.0	3,758.2
	hatch 519.6		hatch 519.6	
No.3	9,510.2	692.6	9,386.6	692.6
	hatch 692.6		hatch 692.6	
No.4	5,826.8	344.4	5,667.0	344.4
	hatch 344.4		hatch 344.4	
No.5	5,522.3	519.6	5,440.2	519.6
	hatch 519.6		hatch 519.6	
Total	4,519.0	26,880.4	4,369.5	25,882.0
	hatch 2,356.9		hatch 2,356.9	
Totals:	33,756.3 m ³		32,608.4m ³	

Grain Stowage @ 1.5 cu.m/tonne: 22,504.2 tonnes

Hold & Tween Deck Measurements:

	Lower Hold	Tween Deck
No. 1 :	Max length 26.46 m Max width 5.0 m at fwd end & 16.8 m at aft end	26.46 m 6.0 m 21.7 m
No. 2 :	Max length 26.46 m Max width 6.0m at fwd end & 10.2 m at aft end (P&S)	26.46 m 11.0 m P&S 11.0 m P&S
No. 3 :	Max length 33.96 m Max width 10.7m at fwd end & 11.1m at aft end (P&S)	--- --- ---
No. 4 :	Max length 19.36 m Max width 11.1m at fwd end & 11.1m at aft end (P&S)	--- --- ---
No. 5 :	Max length 26.46m Max width 8.6m at fwd end & 6.0 m at aft end (P&S)	--- --- ---

Clear Deck Spaces:

Hold	Tank Top		Tween Deck		Weather Deck	
	Area m ²	t/m ²	Area m ²	t/m ²	Area m ²	t/m ²
No. 1	288.4	18	365.6	5	220.7	2
No. 2	2 x 200	18	2 x 291	5	416	2
No. 3	2 x 375	18	-	-	554.2	2
No. 4	2 x 217	18	-	-	275.8	2
No. 5	2 x 152	18	-	-	416	2

All accesses AWWF approved.

SPEED AND CONSUMPTION

Main engine uses MFO 380cst at 50C to ISO 8217 RMG 35 basis operating draft of 10.588m, max. Beaufort 3, sea state 3.

Speed (knots)	18.5
Consumption MT/day	48.0
Diesel Generators	: MFO 380 cst at 50C to ISO 8217 Grade RMG
In port, idle	: 2.0 MT/day
At sea	: 2.3 MT/day
All cranes working	: 3.5 MT/day
50 reefers	: 1.5 MT/day (additional)
100 reefers	: 3.0 MT/day (additional)
150 reefers	: 4.5 MT/day (additional)
Boiler consumption (MFO 380 CST, same as main engine)	
In port	: 1.5 MT/day
At sea	: Nil

CARGO HANDLING EQUIPMENT

Cargo Gear: Five centreline mounted Electro-Hydraulic Deck Cranes;
No 1 Crane; SWL 26t at 4.5 to 23m
No 2 Crane; SWL 35t at 5.0 to 30m
No 3 Crane; SWL 35t at 5.0 to 30m
No 4 Crane; SWL 35t at 4.5 to 24m
No 5 Crane; SWL 26t at 4.0 to 20m

Cargo Lashing Gear :

Below Decks : Twistlocks (Tiger fitting/K-679) for bottom tiers
Twistlocks (semi-Auto/K-2101/1-03-70L) for 2nd 3rd 4th 5th Tiers
On Deck : Twistlocks (p type/k-709-k) for bottom tier
Twistlocks (semi-Auto/K-2101/1-03-70L) for 2nd 3rd 4th Tiers
Lashing rods and turnbuckles.

MACHINERY

Main Engine: 1 x Kobe-Mitsubishi Diesel 8UEC60LS, reversible, 2-stroke diesel engine driving a fixed pitch 5-bladed propeller. Max. continuous rating 19,200 BHP at 100 RPM and normal output 16,320 BHP at 94.7 RPM.

Diesel Generators: 4 x Yanmar, type T240L-ET Generators, each 820KW, 440V, 60 Hz.

Bow Thruster: 1 x 1060 KW Nakashima driving 4 blade controllable pitch propeller

COMPLEMENT

Officers : 10
Crew : 18
Berths : 30
Max LSA capacity : 30

TANK CAPACITIES

MFO : 2,165.20 m³ @ 96%
MDO : 83.55 m³ @ 96%
FW : 279.33 m³ @ 100%
Ballast : 9,436.94 m³ @ 100%

GENERAL

All holds protected by CO₂ smothering & water drenching. Dehumidifiers for holds. Forced draft ventilation - minimum 6 air changes/hour. Bridge equipment to a high standard is fitted, including 2 x GPS Navigator and 2 radars. Communication equipment meets with the latest GMDSS requirements. Vessel is linked to Head Office by the 'Amosconnect' system of data communication, allowing efficient information exchange.



THE CHINA NAVIGATION CO. LTD.



M.V. TASMAN COMMANDER

1257 TEU Geared Multi-Purpose Containership

BUILT

October 1994
Minami Nippon, Usuki Japan
Hull No. M-633
Ex. "Oceanic Challenger"

CLASS

Lloyds +100A1 LMC UMS
IMO No. 9103104

PORT OF REGISTRY

Hong Kong
Off. No. HK-1352

DIMENSIONS

Length O.A. : 184.90m
Length B.P. : 176.00m
Breadth Mld. : 27.60m
Depth Mld. : 14.70m
Summer draft : 10.588m
Summer Dwt. : 25,410mt
GRT : 18468
NRT : 9201
GRT Suez : 19494.59
Panama : 19274.41
NRT Suez : 16747.90

CALL SIGN

VRAE4

COMMUNICATIONS

Fleet 77 : No. 764586923 (Tel)
: No. 764586926 (Fax)
Satcom C : No. 447744050 (Telex)
Sat M : No. 764057540 (Tel)
: No. 764057541 (Fax)
Email : tasmancommander@cnco.amosconnect.com

CONTAINER CAPACITY

Max containers intake : 1193 TEU + 32 FEU = 1257 TEU
Hold : 414 TEU + 32 FEU
Deck : 779 TEU
Total : 1193 TEU + 32 FEU = 1257 TEU

Max 40ft Capacity

Below deck : 198 FEU + 82 TEU
Above deck : 291 FEU + 179 TEU
Total : 489 FEU + 261 TEU (1239 TEU)

Max 20ft Capacity

Below deck : 414 TEU
Above deck : 779 TEU
Total : 1193 TEU

TEU capacity with homogenous load – IMO criteria and approved for dept. condition with 96% bunkers and arrival condition with 15% bunkers.

12T	14T	16T	18T	20T
1119 +	1028 +	956	876	739
32 FEU	32 FEU	32 FEU	32 FEU	32 FEU
1183 TEU	1092 TEU	1020 TEU	940 TEU	903 TEU

FEU capacity with homogenous load - IMO criteria and approved for dept. condition with 96% bunkers and arrival condition with 15% bunkers.

20T	30T
470	404

Permissible uniform distributed load:

Weather deck hatch covers : 2.0 mt per m²
Tweendeck : 5.0 mt per m²
Tank top : 18.0 mt per m²

Permissible Container Stack weights:

Position Hatch Cover Tween Decks Hold Tank Top
TEU's: No.1 Hold 51.2T (Bay 01 & 03) 48T 96T
72T (Bay 05)

No. 2,3,4,5
Holds 75.2T 48T (No.2) 120T

FEU's No. 1 Hold 64.6T 60T 120T
No. 2,3,4,5
Holds 94.5T 60T (No.2) 150T

Poop Deck (Bays 33, 35 & 37) 75.2T -- TEU/FEU

Tween Deck height : 5.94m

Reefer Cargo : 150 reefer sockets, each rated at 440v, 30A, 60Hz

Reefer points situated : On deck 150 points
Maximum reefer load : 150 TEU

M.V. TASMAN COMMANDER

1257 TEU Geared Multi-Purpose Containership

PRINCIPAL DIMENSIONS

LENGTH	(O.A.)	184.90M
LENGTH	(B. P.)	176.00M
BREADTH	(MLD)	27.60M
DEPTH	(MLD)	14.70M
DRAFT	(SUMMER)	10.588M
DEADWEIGHT	(SUMMER)	25,410MT
GROSS TONNAGE		18468
NET TONNAGE		9201
MAIN ENGINE	MITSUBISHI	8UEC 6OLS
	M.C.R.	19,200BHP x 100RPM
	N.O.P.	16,320BHP x 94.7RPM
COMPLEMENT		30P
CLASS		L R
SERVICE SPEED		18.5KTS
CONTAINER	(NOMINAL)	
	HOLD	478TEU
	DECK	779TEU
	TOTAL	1,257TEU
REF. PLUG		150TEU
REF. CONTAINER		150TEU

